

# DIGITAL KEYPAD



**LK-1010-1**

**LK-1010-2**

## FEATURES

- Programmable code number in 1 to 14 figures.
- Code number easily changeable and EEPROM keeps memorized codes permanently even if power supply failed.
- Option of one channel (LK-1010-1) or two channels (LK-1010-2).
- Two kinds/levels of code numbers available at the same time (LK-1010-2)
- Emits electronic beeping every time key-button is depressed.
- Output indication by beeping and by LED lamp.
- With keypad back-lit.
- Tamper switch provided.
- With doorbell push button.
- Easy to install.
- Most suited for remote control of security system, unlocking electric lock or electric shutter, etc.

## SPECIFICATIONS

- Code Number: in 1 to 14 figures
- Power Supply: 10.5- 16V DC
- Power Consumption:
  - (LK-1010-1) Quiescent - 30mA, relay on - 60mA
  - (LK-1010-2) Quiescent - 60mA, both Relay on - 115mA
- Output: Relay contact NO/NC (1A/24V DC or 0.5A/120V AC) Selectable alternate or momentary operation, momentary operate time 1 to 255 seconds programmable
- Tamper Switch: Provided.
- Doorbell Switch: 0.5A/120VAC
- Operation Temperature: -10°C~55°C
- Wiring: Lead wiring (lead length: 22mm)
- Housing: Molded ABS resin
- Dimensions: 130L x 80W x 34H mm



# DIGITAL KEYPAD



**LK-1020-1**



**LK-1020-2**

## FEATURES

- Programmable code number in 1 to 14 figures.
- Code number easily changeable and EEPROM keeps memorized codes permanently even if power supply failed.
- Option of one channel (LK-1020-1) or two channels (LK-1020-2).
- Two kinds/levels of code numbers available at the same time (LK-1020-2)
- Emits electronic beeping every time key-button is depressed.
- Output indication by beeping and by LED lamp.
- With keypad back-lit.
- Tamper switch provided.
- With doorbell push button.
- Easy to install.
- Most suited for remote control of security system, unlocking electric lock or electric shutter, etc.

## SPECIFICATIONS

- Code Number: in 1 to 14 figures.
- Power Supply: 10.5- 16V DC.
- Power Consumption:  
(LK-1020-1) Quiescent - 30mA Relay on - 60mA  
(LK-1020-2) Quiescent - 45mA Both relay on - 80mA
- Output: Relay contact NO/NC (1A/24A DC or 0.5V/120V AC)  
Selectable alternate or momentary operation,  
momentary operate time 1 to 255 seconds programmable
- Tamper Switch: Provided.
- Doorbell Switch: 0.5A/120VAC
- Operation Temperature: -10°C~55°C
- Wiring: Lead wiring (lead length: 22mm)
- Housing: Molded ABS resin.
- Dimensions: 115Lx 115W x 20D mm